




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : F03G 7/06, F23N 3/04	A1	(11) International Publication Number: WO 90/15928 (43) International Publication Date: 27 December 1990 (27.12.90)
(21) International Application Number: PCT/US90/03458 (22) International Filing Date: 19 June 1990 (19.06.90) (30) Priority data: 369,453 21 June 1989 (21.06.89) US (71) Applicant: JOHNSON SERVICE COMPANY [US/US]; 5757 North Green Bay Avenue, Milwaukee, WI 53209 (US). (72) Inventors: ABUJUDOM, David, N., II ; 3220 Pilgrim Road, Brookfield, WI 53005 (US). THOMA, Paul, Edward ; 637 Elm Spring Avenue, Wauwatosa, WI 53226 (US). HAJNY, Roger, Vincent ; 7205 Andover Road, Cedarburg, WI 53012 (US). LINSTEAD, Steven, Allen ; 228 Karin Drive, North Prairie, WI 53153 (US).		(74) Agents: BARRY, Ronald, E.; Foley & Lardner, 777 East Wisconsin Avenue, Milwaukee, WI 53202-5367 (US) et al. (81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent)*, DK (European patent), ES (European patent), FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: A SHAPE MEMORY ACTUATOR**(57) Abstract**

A shape memory actuator for controlling the position of a control member, such as a damper plate (16) in a duct (14), the actuator including first and second shape memory elements (30, 32) each having an austenite phase transition temperature above which each element assumes a predetermined memory shape and a lower phase which forms when said element is stretched from the predetermined memory shape, the first and second elements being connected to move the control member in different directions when one or the other of the elements are heated to a temperature above its austenite phase transition temperature and an electrical circuit (35) for selectively raising the temperature of one or the other of the elements. The control member may be held in a position between full open and full closed by holding mechanisms which connect the actuator to the control member. The holding mechanisms include a video elastic mechanism, a positive interlock mechanism that is released by a shape memory element, or a magnetic member formed of alternately arranged magnetic poles. A number of connectors are disclosed for connecting the SMA members to the dampers.

DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MC	Monaco
AU	Australia	FI	Finland	MG	Madagascar
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Fasso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greece	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
DK	Denmark			US	United States of America

A SHAPE MEMORY ACTUATOR

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a
bidirectional shape memory actuator having specific
physical and mechanical properties and, more
particularly, to the positioning of a moveable member,
such as a vent control, using a shape memory actuator.

Description of the Prior Art

10 Shape memory elements have been used to open
and close vent dampers as shown and described in U.S.
Patent No. 4,284,235 entitled "Vent Control Arrangement
for Combustion Apparatus" issued on August 18, 1981.
In the arrangement disclosed in this patent, a helix
15 made of a shape memory material is used to open a
damper plate. The damper plate is normally in a closed
position and opened by heating the helix to the
deformation temperature so that it deforms to rotate
the damper plate to a fully opened position. A lever
20 mounted on the helix, on reaching the fully open
position, closes a limit switch that activates a
solenoid actuated gas valve to light the burner. The
helix remains energized until the heat requirement is

-2-

satisfied. The holding circuit is then opened. As the helix cools down, it will rotate the damper to the closed position.

5 In a device of the type shown in U.S. Patent application serial no. 276,698 entitled "Personal Environmental Module" filed on November 28, 1988, and assigned to the same assignee, dampers are used to control the air flow rate of cool air and room air into the module to meet the personal requirements of the individual working in the work station. In this type of device motor controllers were used to control the position of the damper plates and thus the temperature and air flow rate of the air passing through the dampers. 10 Accurate control of the position of the damper plate is critical to the success of the module. The electric motors have a limited life, are noisy and expensive and also require periodic maintenance. 15

SUMMARY OF THE INVENTION

20 In the present invention, a shape memory actuator having two shape memory elements is used to control the position of a damper plate in both opening and closing the damper. Using two shape memory elements makes it possible to positively locate a damper plate in a duct at different positions and thereby control the air flow rate through the duct to satisfy conditions of temperature and pressure. The shape memory elements can be directly incrementally heated to move the damper plate in the duct to positions intermediate full open and full closed. It should be noted that while the following description is with respect to the control damper plate in an air flow duct, the invention is not 30 so limited. The shape memory actuator can be used to

-3-

position any fluid control member, whether liquid or gas, where the control member is moved in one direction to an open position and another direction to a closed position.

5 The two shape memory elements, each have a predetermined shape memory austenite or upper phase transition temperature and a predetermined martensite or lower phase transition temperature, one of the shape memory elements being connected to move the damper plate
10 toward an open position when the temperature of the shape memory element is raised to the austenite or upper phase transition temperature and the other actuator being connected to move the damper plate toward the closed position when the temperature of the second shape
15 memory element is raised to the austenite or upper phase transition temperature. The shape memory elements can be heated directly or indirectly to move the damper plate to meet the required air flow rate conditions.

 One of the principal features of the invention
20 is the ability to hold a damper plate in a position between full open and full closed without a holding current in the shape memory elements.

 One of the features of the invention is the provision of a holding device which may be in the form
25 of a visco elastic mechanism, brake mechanism or a magnetic stepping mechanism to hold the damper plate in a particular position in a duct.

 Another feature of the invention is the use of Shape Memory Alloy Rotating Terminal (SMART)
30 connectors for connecting the shape memory elements to the damper plate and to fixed or stationary mounting pins. These connectors have a low mass to avoid heat sinking at the ends of the shape memory elements, act

-4-

as electric couplers and provide for rotary motion of the connector at the point of connection.

5 A principal advantage of the invention is the provision of a shape memory actuator that is simple in structure and operation in comparison to motor controlled systems as well as being noiseless in operation.

Another advantage of the invention is the elimination of drive motors, gears, and the like presently used as damper controllers.

10 Other principal features and advantages of the invention will become apparent to those skilled in the art upon review of the following detailed description, claims and drawings.

DETAILED DESCRIPTION OF THE DRAWINGS

15 Figure 1 is a perspective view of a fluidic damper using the shape memory actuator according to the invention to control the position of the damper plate in the duct.

20 Figure 2 is a top view of the fluidic damper of Figure 1 showing the position of the shape memory actuator.

Figure 3 is a view of the shape memory actuator showing the damper plate in the partially open position.

25 Figure 4A is a view similar to Figure 3 showing the damper in the closed position.

Figure 4B is a view similar to Figure 3 showing the damper in the full open position.

Figure 5 is a schematic diagram of an electrical circuit for the shape memory actuator.

-5-

Figure 6 is a view of the shape memory actuator showing the shape memory elements connected to a visco elastic drag assembly for positively positioning the damper plate in a duct.

5 Figure 7 is a view of the shape memory elements connected to a damper plate through a shape memory controlled brake mechanism for maintaining the position of the damper plate in a duct.

10 Figure 8 is a view similar to Figure 7 showing the shape memory elements connected to a damper plate through a spring controlled brake mechanism for controlling the position of the damper plate in a duct.

15 Figure 9 is a view of the shape memory elements connected to a damper plate through a magnetic stepping mechanism for positively locating the position of the damper plate in the duct.

Figure 10 is a view of the top of an air flow duct using a rotary magnetic stepping mechanism for controlling the position of the damper plate.

20 Figure 11 is a perspective view of a Shape Memory Alloy Rotating Terminal (SMART) connector shown mounted on the first turn of a shape memory coil.

Figure 11a is a side plan view of the connector shown in Figure 11.

25 Figure 12 is a view of the SMART connector shown in Figure 11a mounted on each end of a coil spring type shape memory element.

30 Figure 13 is a view of the shape memory element of Figure 12 rotated 90° to show the connection to the pin of the damper plate lever and stationary pin.

-6-

Figure 14 is a perspective view of a non-conductive connector for a coil spring type shape memory element.

5 Figure 15 is a view, similar to Figure 14, showing a non-conductive connector having a portion of the thread broken away to provide for connection of the coil type element to the connector.

10 Figure 16 is a view showing another form of mounting for the coil type element to the non-conductive terminator.

Before the invention is explained in detail, it is to be understood that the invention is not limited in its application to the details as set forth in the following description or illustrated in the drawings.
15 The invention is capable of other embodiments and of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

20 DESCRIPTION OF THE INVENTION

Referring to Figures 1, 2, and 3 of the drawings, a shape memory actuator 10 according to the invention is shown for controlling the position of a damper plate 12 in a duct 14. The damper plate 12 is
25 secured to a rod 16 by means of a set screw 28. One end of the rod is mounted for rotary motion in a bearing 18 and the other end in a bearing block 20. One end of the rod 16 is connected to the shape memory actuator 10. The other end of the rod extends outwardly from
30 the bearing block 20 and is secured in the block 20 by a retaining ring 22 and a set screw 24.

-7-

In accordance with the invention, the shape memory actuator 10 includes a first means in the form of a shape memory element 30 for opening the damper plate 12 and a second means in the form of a shape memory element 32 for closing the damper plate 12. The shape memory elements 30 and 32, as shown in Figures 1, 2, and 3, are in the form of coil springs, however, it should be noted that the shape memory elements can be provided in various forms or configurations. The element 30 is connected at one end to a pivot pin 44 mounted on the end of a lever 36 which is secured to the rod by a screw 38. The other end of the shape memory element 30 is connected to a fixed pivot pin 40. The element 32 is connected to pivot pin 44 and to a fixed pivot pin 42.

The shape memory elements 30 and 32 are made of the same shape memory alloy so that they have essentially the same hysteresis and phase characteristics. Shape memory alloys, as described herein, are of the type described in U.S. Application Serial No. 183,818 filed on April 20, 1988, entitled "A Method For Producing A Shape Memory Alloy Member Having Specific Physical and Mechanical Properties" which is assigned to the same assignee and is incorporated herein by reference. In that application, a method is described for providing specific physical and mechanical properties for shape memory alloy materials. These properties relate to the transformation temperatures of the various shape memory phases, the resulting hysteresis between such phases, and the relationship between the start and finish temperatures of the respective phases. Although the same alloy is described herein, it is within the contemplation of the

-8-

invention to use different shape memory alloys as well as alloys having different characteristics for each of the shape memory elements.

5 Referring to Figure 4A, it should be noted that the shape memory element 30 has been heated to a temperature at or above the austenite phase transition temperature, and the element has assumed the tight coil spring memory shape. As the element 30 assumes the tight coil spring shape the damper 12 is closed and the
10 element 32 is stretched mechanically transforming element 32 from a austenite phase A to a martensite phase, M. When the shape memory element 30 cools after being transformed to the austenite or upper phase A, the element 30 will remain in the austenite phase until
15 the element 32 is heated to open the damper. As the element 32 is heated above its austenite phase transition temperature, it assumes the tight coil memory shape, Figure 4B. The cooled element 30 will be stretched to mechanically transform the element 30 from
20 the austenite phase to the martensite phase.

Certain thermo mechanically processed shape-memory alloys transform from the austenite phase to the martensite phase by first transforming to a rhombohedral phase and then transforming to the martensite phase.

25 It is important in the transformation of the elements 30 and 32 from the austenite to the martensite phase, that the transformation is mechanically induced by stretching and not thermally induced by cooling. The life of the SMA spring is reduced if the element is
30 initially thermally induced to the martensite phase and then reoriented when mechanically stretched by the

-9-

other element. This is prevented by selecting an SMA alloy that is compatible with the expected environmental conditions.

5 It should be noted that in the operation of the damper control two elements, 30 and 32, are used. When one element is heated to open or close the damper, the second element will be stretched by the contracting motion of the first element. In either case, once the damper is opened or closed, the heated element is allowed
10 to cool down no farther than the start of the unstressed martensite phase.

It is also possible to partially open or close the damper. In this regard, one of the elements 30 or 32 can be incrementally heated up to obtain partial
15 austenite transformation. The second of the elements will be stretched, to partially induce martensite transformation. If it is desired to open the damper farther, the same element can be heated again to obtain the desired increase in the opening. If it is desired
20 to move the damper in the opposite direction, the second element can be heated to obtain partial or complete austenite transformation to move the damper in the opposite direction. It should be noted that both of the elements may not be simultaneously heated to the
25 austenite phase. In partial transformation, both phases may co-exist in the same element.

The shape memory elements 30 and 32 are energized by means of an electrical controller circuit 35 as shown in Figure 5. The shape memory elements 30
30 and 32 are connected across a power source 37 and in series with solid state switches (triacs) 39 and 41. Each switch 39, 41 being controlled by controller 43. When the controller responds to a signal to increase or

-10-

decrease the air flow through the duct 14, one of the switches 39 or 41 is activated to close the circuit for one of the shape memory elements 30, 32. The energized shape memory element will move to its memory shape moving the damper plate in the opening or closing direction. When the damper plate reaches the desired position, the controller will turn off the switch. Once the switch is turned off, a time delay is initiated by the controller preventing the energization of the other switch until the previously energized element has cooled down to a temperature that permits the mechanical induction of the martensite phase.

In operation, the first shape memory element 30 is energized to close the damper plate 12. As seen in Figure 4A, the first element 30 will contract and the second shape memory element 32 will be stretched by the contraction of the first element 30. The damper is opened by heating element 32. As seen in Figure 4B, the element 32 contracts and the element 30 is stretched by the contracting motion of element 32.

If the damper is to be partially opened as shown in Figure 3, the element 30 is heated long enough to move the damper plate 12 incrementally to the desired setting and then de-energized.

A balance of forces is achieved between the stress imposed on the heated element as it contracts and is transformed to the austenite phase while the other element is stretched mechanically inducing the martensite phase in the other element.

When the element 30 is de-energized, the element 30 may have sufficient spring force to move the damper plate 12 slightly in the opposite direction.

-11-

Means are therefore provided for holding the damper plate 12 in the position to which it was moved by the energized element.

5 In this regard and referring to Figures 6 through 10, a number of shape memory actuators are shown which include means for holding the damper plate 12 in a fixed position with respect to the duct 14. As seen in Figure 6, the shape memory elements 30, 32 are connected to a drag assembly 44 which is used to hold
10 the damper plate 12 in a particular position. The drag assembly 44 includes a pinion gear 46 mounted on the rod 16 and a rack 48 provided on an elongate member 50 which is connected at each end to the elements 30, 32. A fixed member 52 is located in abutting relation to
15 the member 50. A viscoelastic material 54 is provided between the elongate members 50, 52 to slightly resist sliding motion between the members 50, 52.

In operation, one of the elements 30, 32, is energized so that it starts to heat up. As it passes
20 through the austenite start transition temperature, the element will start to move toward its memory shape configuration pulling the elongate member 50 toward the energized element. The de-energized element will stretch and the damper plate 12 will move toward the
25 open or closed position. When the damper plate 12 reaches the desired position, the energized element is de-energized. The stretched element will try to pull the member 50 slightly backward. The visco elastic material will hold the elongate member 50 in a fixed
30 relation with respect to the fixed member 52 so that the damper plate 12 remains in the fixed or desired position.

-12-

Referring to Figure 7, another form of holding means is shown which includes an elongate member 50' having a rack 48 on one surface of the member 50' which is positioned to engage the pinion gear 46. A series of depressions 56 are provided on the opposite surface of the member 50'. A fixed member 52' is positioned next to member 50' and is provided with a bore 58 that houses a stop pin 60. The pin 60 is biased into engagement with the elongate member 50' by means of a spring 62 which bears against a plate 64 provided on the pin 60. The pin is retained within the bore by means of a retaining ring 66 provided in a groove 63 in the open end of the bore 58. The pin 60 is withdrawn from the elongate member 50' by means of a shape memory element 68 which is connected to the end of the pin 60 and to a fixed pin 70.

Whenever the damper plate 12 is to be moved to a new position, one of the elements 30, 32 will be energized and the element 68 will also be energized. When the damper plate 12 reaches the desired position, both the energized element and the element 68 will be de-energized so that the spring 62 will bias the pin 60 into engagement with the corresponding depression 56 to lock the member 50' in a fixed position.

In the embodiment of the invention shown in Figure 8, the elongate member 50'' includes a rack 48 which is positioned to engage the pinion gear 46. A ratchet gear 72 is provided on the bottom of the member 50''. The stationery member 52'' includes a pin 60, spring 62 and plate 64 as described above. The pin 60 is in the form of a pawl which is biased by means of a spring 62 into engagement with the gear 72. When the element 30 is energized, the elongate member 50'' will

-13-

be moved to the left and the pawl 60 will snap from one gear to the next in the gear 72 and thereby retain the member 50'' in position when the element 30 is de-energized.

5 In Figures 9 and 10 step by step holding means are shown in the form of an elongate magnetic assembly 80 (Figure 9) and a circular magnetic assembly 90 (Figure 10). As seen in Figure 9, the elongate member 50''' has a rack 48 positioned to engage the pinion gear 46.

10 The member 50''' is made up of alternate north and south magnetic pole pieces 47 and 49, respectively. A fixed member 52''' is also made up of alternate north and south pole pieces 51 and 53, respectively. When one of the shape memory actuators is heated, the elongate member

15 50''' will be moved to the right or left with respect to the fixed member 52''. When the shape memory element is de-energized, the member 50''' will move to align the north pole 47 and south pole 49 with the corresponding south pole 53 and north pole 51 on member

20 52'''.

 In Figure 10 a duct 14 is shown of the type shown in Figure 1 and 2 in which the step by step holding means is in the form of circular magnetic members 92 and 94 which are used to control the position of the

25 damper plate 12. The member 92 having alternate north and south poles 91, 93, respectively. The member 94 having alternate north and south poles 95, 97, respectively. The member 92 is mounted on the duct 14 and the member 94 is mounted on the end of the rod 16.

30 On energization of one of the elements 30 or 32, the member 94 will rotate to a position wherein the north

-14-

and south poles of member 94 are opposite the south and north poles of member 92 when the actuator is de-energized.

5 The elements 30 and 32 can be connected to the fixed pins and moveable members by means of shape memory alloy rotational terminal (SMART) connectors 100. The shape memory elements 30 and 32 are shown in the form of coils in Figures 11, 12, and 13. This form is used because it provides the least amount of stress in the actuator. It is important to provide a connector that requires a minimum amount of the turns of the coil for mechanical and electrical connection and is of small mass and low thermal conductivity to prevent heat sinking at the ends of the coil. It is important to minimize heat sinking in the connectors so that there is equal strain between each loop when heated and cooled as shown in Figure 13.

This is accomplished by using SMART connectors 100 which are stamped from sheet stock in the form of a flat strip of material having a low mass. The connector 100 is provided with a pair of legs 104 at one end and a hook 106 at the other end. A hole 108 is provided in the center of the strip for connecting the connector to an electrical lead 112. The SMART connectors are connected to the last turn of the coil at each end of the shape memory elements 30 and 32. The connectors are mounted on the coil by inserting the projection 101 at the end of the connector into the coil and wrapping the legs 104 around the coil thus providing both a mechanical and electrical connection to the element. The hole 108 provides a connection for the electric leads 112.

-15-

In Figures 14, 15 and 16 a spring shape memory alloy link (SSMAL) connector 120 is shown as an alternate means for connection to the element. The link connector is made out of a material which is electrically and thermally non-conductive so that there is no heat sink formed at the end of the coil. The link connector 120 is in the form of a rod 122 which is threaded either totally or partially with a square thread 124 that is matched to the SMA member turns per inch. The diameter of the rod 122 is measured from the bottom of the thread and is the same or slightly larger than the inside diameter of the coils of the shape memory element 126.

The materials which can be used for this type of link are engineering thermoplastics. Means can be formed on the end of the rod 122 for attaching the connector 120 to a pivot member. Such means is in the form of a hook 127, secured to or molded on the end of rod 122.

Means are provided at the end of the thread 124 for forming a solid, inflexible point of egress 130 for the element 126. Such means is formed at the end of the rod 122 by removing a portion of the thread at the spring end of the rod 122. The portion is removed for one-fourth of one revolution from the normal end of the thread. This provides a solid, inflexible point of egress 130 for the element 126 when wound on the link connector.

Means can be provided on the threads of the link connector for covering the turns of the coil in the spaces between the threads on the connector so that they cannot unwind. Such means is in the form of a non-flowing, high peel strength epoxy 132 applied in

-16-

the spaces between the threads where the coils of the element have been wound as shown in Figure 15.

Referring to Figure 16, a modified form of link connector 120 is shown in which a portion of the thread 124 is removed to form a space 125 to facilitate the application of the epoxy 132 so that the epoxy does not contact the active portion of the coils of the element 126. The active portion of the element 126 begins at the point of egress 130.

Thus, it should be apparent that there has been provided, in accordance with the invention, a shape memory actuator for controlling the position of a fluid control member in a duct that fully satisfies the aims and advantages set forth above. While the invention has been described in conjunction with specific embodiments thereof, it is evident that there are many alternatives, modifications, and variations that will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications, and variations as fall within the spirit and broad scope of the appended claims.

CLAIMS

- 1 1. A shape memory actuator for controlling the
2 position of a damper plate in a duct, said actuator
3 comprising:
4 a first shape memory element having an
5 austenite phase transition temperature above which said
6 first element assumes a predetermined memory shape and a
7 stress induced martensite phase which forms when said
8 element is stretched from said predetermined memory
9 shape, said first element being operatively connected to
10 move the damper plate toward a fully opened position when
11 the temperature of said first element is raised to or
12 above its austenite phase transition temperature;
13 first means for selectively raising the
14 temperature of said first element;
15 a second shape memory element having an
16 austenite phase transition temperature above which said
17 second element assumes a predetermined memory shape and
18 a stress induced martensite phase which forms when said
19 second element is stretched from said predetermined
20 memory shape,
21 said second element being operatively connected
22 to move the damper plate toward a fully closed position
23 when the temperature of said second element is raised to
24 or above its austenite phase transition temperature;
25 and second means for selectively raising the
26 temperature of said second element.
- 1 2. The actuator according to claim 1 including
2 means for holding the damper plate in an intermediate position
3 between fully open and fully closed when said first or second
4 temperature raising means is stopped.

-18-

1 3. The actuator according to claim 2 wherein said
2 holding means includes a viscoelastic material for imposing a
3 drag on the damper plate whereby said damper plate will remain
4 in a fixed position when said first or second element is
5 cooled.

1 4. The actuator according to claim 2 wherein said
2 holding means comprises a first elongate member operatively
3 connected to the damper plate and to said shape memory
4 elements, said first member having a series of recesses on one
5 side, and a second fixed member disposed in a spaced relation
6 to said first member, means mounted in said second member for
7 movement into engagement with one of said recesses in said
8 first member whereby said first elongate member cannot move
9 and shape memory means having an upper phase transition
10 temperature above which said shape memory means assumes a
11 predetermined memory shape, said shape memory means
12 disengaging said engaging means from said first member when
13 the temperature of said shape memory means is above its upper
14 phase transition temperature.

1 5. The actuating device according to claim 2
2 wherein said holding means comprises a first elongate member
3 operatively connected to the damper plate and having ratchet
4 teeth along one side, means positioned next to said first
5 elongate member for engaging said teeth and means for biasing
6 said engaging means into engagement with said teeth to prevent
7 movement of said first member.

1 6. A shape memory actuator for positioning a
2 control member, said actuator comprising:
3 a first shape memory means for moving the control
4 member in one direction;
5 a second shape memory means for moving the control
6 member in the other direction;

-19-

7 said first means including an electrically
8 conductive shape memory element having predetermined upper and
9 lower phase transition temperatures, said first element
10 assuming a predetermined memory shape when electrically heated
11 to said upper phase transition temperature, said second means
12 including an electrically conductive shape memory element
13 having predetermined upper and lower phase transition
14 temperatures, said second element assuming a predetermined
15 memory shape when electrically heated to said upper phase
16 transition temperature; and
17 means for electrically energizing one of said
18 elements to its upper phase transition temperature, said
19 elements being connected to the control member so that the
20 energized element in assuming its memory shape pulls the other
21 element out of its memory shape whereby the control member
22 will be moved in said one or said other direction and said
23 other element is mechanically transformed to its lower phase
24 temperature.

1 7. The actuator according to claim 6 including
2 means for holding the control member in a fixed position when
3 the heated element is allowed to cool.

1 8. The actuator according to claim 7 wherein said
2 holding means comprises a first elongate member operatively
3 connected to the control member and to said first and second
4 shape memory elements, a second fixed elongate member
5 positioned in close proximity to said first elongate member
6 and a viscoelastic material positioned between said elongate
7 members to impose a drag on the movement of said first
8 elongate member with respect to the fixed elongate member when
9 the temperature of said first or second shape memory element
10 cools whereby the control member will be held in a fixed
11 position.

-20-

1 9. The actuator according to claim 6 including
2 electrically conductive means connecting one end of said first
3 and second shape memory means to the control member and the
4 other ends to fixed pivot pins.

1 10. The actuator according to claim 9 wherein said
2 conductive means comprises a thin flat strip having a pair of
3 legs at one end and a curved hook at the other end, said legs
4 being connected to said shape memory elements and said curved
5 hook being connected to the control member and to said pivot
6 pins.

1 11. A shape memory actuator for controlling the
2 position of a control member, said actuator comprising:
3 a pair of electrically conductive shape memory
4 elements, one of said elements being connected to move the
5 control member toward an open position and the other of said
6 elements being connected to move the control member toward a
7 closed position,
8 each of said elements having a shape memory
9 transition temperature above which said elements assume their
10 memory shape, and a lower temperature below which they can be
11 stretched from their memory shape, said elements being
12 connected to the control member so that the electrically
13 energized element pulls the other element from its memory
14 shape to a stretched shape and means for selectively
15 electrically energizing one or the other of said elements to
16 open or close the control member.

1 12. A shape memory actuator for incrementally
2 positioning a control member, said actuator comprising:
3 a pair of electrically conductive shape memory
4 elements, the first of said elements being connected to move
5 the control member toward a first position and the second of
6 said elements being connected to move the control member

-21-

7 toward a second position; and each of said elements having an
8 austenite phase and a lower temperature phase whereby the
9 stresses in said elements are balanced in any position of the
10 control member.




FIG. 1




FIG. 4A




FIG. 4B




FIG. 3







FIG. 2

2/5



SUBSTITUTE SHEET

3/5




FIG. 9




FIG. 10

4/5




FIG. 11A




FIG. 11




FIG. 12




FIG. 13







FIG. 5

5/5




SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

PCT/US 90/03458

International Application No

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.C1. 5 F03G7/06 ; F23N3/04		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.C1. 5	F23N ; F03G	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	GB,A,2148444 (THE FURUKAWA ELECTRIC COMPANY) 30 May 1985 see the whole document ---	1, 6, 11, 12
X	GB,A,2168810 (KABUSHIKI KAISHA TOKAI RIKI DENKI SEISAKUSHO) 25 June 1986 see the whole document ---	1, 6, 11
X	PATENT ABSTRACTS OF JAPAN vol. 9, no. 297 (M-432)(2020) 25 November 1985, & JP-A-60 135673 (KOJIMA PRESS KOGYO) 19 July 1985, see the whole document ---	1, 6, 11, 12
A	EP,A,173433 (B.S.G. OVERSEAS LIMITED) 05 March 1986 see page 3, line 7 - page 4, line 20; figures --- -/-	2, 3, 7
<p>¹⁰ Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
26 SEPTEMBER 1990	24 OCT 1990	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	KOOIJMAN F.G.M. 	

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
P,A	WO,A,8909880 (KONI) 19 October 1989 see abstract; figures ---	1-4, 7
A	SOVIET INVENTIONS ILLUSTRATED Section_, week 8838,02 nov 1988 Derwent Publications Ltd., London GB. * Q55,no 88-269069/38 * & SU,A,1377450 (LENGD SHIP-BUILDING) 05.05.1986 ---	4, 5, 7
A	US,A,4284235 (DIERMAYER ET AL.) 18 August 1981 see abstract; figures (cited in the application) ---	1
A	US,A,4700541 (GABRIEL ET AL.) 20 October 1987 ---	

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.**

US 9003458

SA 38206

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

02/10/90

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB-A-2148444	30-05-85	JP-A- 60186779	24-09-85
		JP-A- 60053676	27-03-85
		DE-A- 3432134	21-03-85
GB-A-2168810	25-06-86	DE-A, C 3539559	22-05-86
		US-A- 4736587	12-04-88
EP-A-173433	05-03-86	JP-A- 61044044	03-03-86
WO-A-8909880	19-10-89	NL-A- 8800944	01-11-89
US-A-4284235	18-08-81	DE-A, C 3046531	27-08-81
		NL-A- 8006779	16-07-81
US-A-4700541	20-10-87	JP-A- 63109285	13-05-88

EPO FORM P0079

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82